


LOCK BOLT

Reference Chart



WARNINGS:

- Do not use a lock longer than the lug bolt being used on the wheel.
- Do not use a lock with a different seat size or style than the lug bolt being used on the wheel.
- Do not use more than one lock per wheel.



Cone Seat Lock Bolts

THREAD SIZE (MM)	OVERALL LENGTH INCHES (MM)	SHANK LENGTH INCHES (MM)	KEY HEX SIZE INCHES (MM)	PART NO
M12 x 1.5 Tuner Wheels	2.02" 51.3	0.95" 24.0	17	27192
M12 x 1.5 Tuner Wheels	2.22" 56.4	1.16" 29.6	17	27191
M14 x 1.5 Tuner Wheels	1.98" 50.3	0.95" 24.0	17	27200
M14 x 1.5 Tuner Wheels	2.20" 55.9	1.16" 29.6	17	27201
M12 x 1.25	2.08" 52.8	1.20" 30.5	3/4" 19	27169
M12 x 1.5	1.68" 42.7	0.81" 20.6	13/16" 21	27100
M12 x 1.5	1.81" 46.1	0.87" 22.1	17	27204
M12 x 1.5 black	1.95" 49.5	1.00" 25.5	17	27178
M12 x 1.5	1.95" 49.5	1.00" 25.5	17	27179
M12 x 1.5	2.19" 55.6	1.31" 33.3	17	27015
M12 x 1.5	2.40" 61.0	1.49" 37.9	13/16" 21	27111
M12 x 1.5	2.53" 64.3	1.66" 42.1	17	27013
M12 x 1.5	2.81" 71.4	1.94" 49.2	17	27014
M12 x 1.75	2.59" 65.8	1.18" 30.0	3/4" 19	27186
M14 x 1.25	1.99" 50.5	1.08" 27.3	17	27226
M14 x 1.5	1.98" 50.3	1.06" 27.0	17	27222
M14 x 1.5	2.06" 52.3	1.18" 30.0	17	27181
M14 x 1.5	2.27" 57.7	1.29" 32.6	3/4" 19	27000
M14 x 1.5	2.27" 57.7	1.29" 32.6	17	27205

Radius Seat Lock Bolts

THREAD SIZE (MM)	RADIUS DIM. (MM)	OVERALL LENGTH INCHES (MM)	SHANK LENGTH INCHES (MM)	KEY HEX SIZE (MM)	PART NO
M12 x 1.5	12	1.54" 39.1	0.81" 20.6	17	28176
M12 x 1.5	13	1.68" 42.7	0.92" 23.3	17	28175
M12 x 1.5	12	1.87" 47.5	1.10" 27.9	17	28172
M12 x 1.5	12	2.34" 59.4	1.57" 39.9	17	28023
M14 x 1.5	14	1.82" 46.2	1.00" 25.4	17	28174
M14 x 1.5	13	1.84" 46.7	1.05" 26.7	17	28018
M14 x 1.5	12	2.06" 52.4	1.25" 31.8	17	28020
M14 x 1.5	12	2.17" 55.1	1.36" 34.5	17	28032
M14 x 1.5	14	2.59" 65.8	1.77" 44.5	17	28017